

VFFS ADM-H390

Features

- Stainless Steel Construction
- Servo Motor Controlled Film Pull Belts
- Panasonic Touch Screen Operator Interface
- Panasonic PLC - Based Control System
- Automatic Program Set-Up
- Instant Program Changeover
- Mark sensor (Fiber Optic) Registration Control
- Quick Change Former Assembly
- Product Clamp and Settler
- Full Safety Guarding and Interlocks (option)
- CE Approved Electrical



Optional Elements

- Gas flushing (Air or Nitrogen gas)
- Re-closable zipper
- Gusseted device
- Air expeller
- Hole punch device
- Material stopper
- Bag support
- Polyethylene sealing system
- Vacuum bag system

Model	ADM-H390	ADM-H390 PE
Bag type	Pillow bag, gusseted bag	Pillow bag, gusseted bag
Bag size	390(W) x 480(L)	390(W) x 480(L)
Speed	40 bags per min	15 bags per min
Power supply	220V 50Hz 4Kw	220V 50Hz 4Kw
Air pressure	0.7m3/min 0.6Mpa	0.7m3/min 0.6Mpa
Weight	980kg	980kg



ADM Packaging Technology P/L

3 Kerr Street, Preston, Vic, 3072, Australia

Ph: 03 9484 8791 Fax: 03 9484 7506

Email: info@admpt.com.au Website: www.admpt.com.au