

VFFS ADM-H590

Features

- Stainless Steel Construction
- Servo Motor Controlled Film Pull Belts
- Panasonic Touch Screen Operator Interface
- Panasonic PLC - Based Control System
- Automatic Program Set-Up
- Instant Program Changeover
- Mark sensor (Fiber Optic) Registration Control
- Quick Change Former Assembly
- Product Clamp and Settler
- Full Safety Guarding and Interlocks (option)
- CE Approved Electrical
- Can use two heating modes for the thermal sealing of laminated film (standard version) or single-layer film (H-1200PE).
- Metering by volume, Auger filler or by weight can be implemented with different options.
- Suitable to packing of various granular or powdered materials, dilated foodstuff.

Specifications

Model	ADM-H590	ADM-H590 PE
Bag type	Pillow bag, gusseted bag	Pillow bag, gusseted bag
Bag size	590(W) x 680(L)	590(W) x 680(L)
Speed	30 bags per min	12 bags per min
Power supply	220V 50Hz 6Kw	220V 50Hz 6Kw
Air pressure	1.0m ³ /min 0.6Mpa	1.0m ³ /min 0.6Mpa
Weight	1200kg	1200kg



ADM Packaging Technology P/L

3 Kerr Street, Preston, Vic, 3072, Australia

Ph: 03 9484 8791 Fax: 03 9484 7506

Email: info@admpt.com.au Website: www.admpt.com.au