

ADM Vertical Form Fill Seal



Feature:

- Stainless Steel Construction
- Servo Motor Controlled Film Pull Belts
- Servo Motor Controlled Jaw Seal Actuation
- Panasonic Touch Screen Operator Interface
- Panasonic PLC - Based Control System
- Automatic Program Set-Up
- Instant Program Changeover
- Mark sensor (Fiber Optic) Registration Control
- Quick Change Former Assembly
- Product Clamp and Settler
- Full Safety Guarding and Interlocks (option)
- CE Approved Electrical

Optional Elements

- Polyethylene seal systems
- Material stopper
- Load shelf for heavy bag support
- Re-closable zipper
- Nitrogen gas flush systems
- Hole punch (Round or Euro)
- Vacuum assist units
- Static eliminators
- Gusseted device
- Special Power Requirement
- Special End-Seal Configurations

Model	ADM-X240	ADM-X285
Bag type	Pillow bag, gusseted bag	Pillow bag, gusseted bag
Bag size	75-240(W) x Up to 300(L)	90-285(W) x Up to 330(L)
Speed	Max:100bpm (Single pull)	Max: 50bpm (Double pull)
Power supply	240V 50Hz 3.5Kw	240V 50Hz 4Kw
Air pressure	0.2m3/min 0.6Mpa	0.2m3/min 0.6Mpa
Packing size	1650x1300x1700	1680x1400x1850



ADM Packaging Technology P/L

3 Kerr Street, Preston, Vic, 3072, Australia

Ph: 03 9484 8791 Fax: 03 9484 7506

Email: info@admpt.com.au Website: www.admpt.com.au